# LITECRAFT OUTLED AT60.ZOOM



The OutLED AT60.zoom is the first product in LITECRAFT's new AT60 series that includes several newcomers. Thanks to its 60 watt chip from OSRAM with RGBW colour mixing, this LED spotlight constitutes a single point light source, making natural shadow formation possible. So as to be able to adjust to changing lighting situations, the OutLED AT60.zoom possesses a continuously adjustable, motorized zoom, which, with its range of 5,5 to 40 degrees, makes both a focused beam and homogeneous wash light possible. Special attention was given in the development of the high-quality optics to achieving the best possible colour mixing in all emission areas. Control comes via DMX512 in 8- or 16-bit resolution according to choice. The IP 65 protected chassis is equipped with powerCON True1 as well as IP XLR 5-pin plug-in connectors.

### Order Code

184851

# **Optical System**

Optics	zoomable optical systems
Beam angle	5,5°-40°, continuous, motor

# **LED Light Sources**

LEDs	1× 60 W COB LED
Colours	$1 \times \text{ red}$ , $1 \times \text{ green}$ , $1 \times \text{ blue}$ , $1 \times \text{ white}$
LED lifetime	> 50.000 hours
Colour mixing system	RGBW

## **Temperature Ranges**

Ambient temperature	-20°/+35°C
Operating temperature	max. 78°C
Cooling	fan, temperature-controlled

# **Controlling and Programming**

Protocol	DMX 512
DMX 512 channels	5/7/10/11/13/17 (6 modes)
Internal memory	audio/stand-alone programs
	fixed colours
	master/slave configuration
Menu display	16-digit, 3-line OLED
DMX 512 connection	XLR 5-pin

### **Technical Details**

Mains	100-240 V 47-63 Hz
Power consumption	0.4 A @ 230 V

# Housing

Material	die-cast aluminium
Colour	black
Protection class	IP 65

# **Dimensions/Weight**

Dimensions (L $\times$ W $\times$ H)	26 × 18,6 × 37 cm
Weight	5,5 kg
Assembly	compact y-yoke for hanging
	and standing use

# **Special Features**

- RGBW in one optical system
- pre-programmed colour macros
- last operating state memory
- selectable dimming curves
- selectable PWM Frequenz
- flicker-free
- operating time counter
- default set function
- powerCON True1 IN/OUT
- waterproof XLR 5-pin plug connector

# **Included Accessories**

• powerCON True1 cable

# **Recommended Accessories**

- LITECRAFT hexa flightcase
- LITECRAFT hexa add-on