

# LITECRAFT

## OUTLED AT10.PLUS



Building on the successful OutLED AT10, LITECRAFT is presenting in the OutLED AT10. plus a product that is at once both successor and complement to the previous model. We say this because all the features of the predecessor series have been retained but improved upon.

So the OutLED AT10.plus convinces with higher light output despite comparable values for colours and emitting characteristics whilst remaining, like its predecessor, completely homogeneous in its colour mixing. For the purpose of control, the device offers identical DMX modes as well as macros and programs. A further plus is the Remote Device Management (RDM) functionality, which makes it possible for settings such as DMX mode and DMX addresses to be undertaken externally via the DMX lead.

When it comes to connectivity, the OutLED AT10.plus has been completely redesigned. Instead of the fixed connector cable, water-proof powerCON True1 and XLR 5-pin connectors are now provided. These make the luminaire still more versatile in its range of applications as well as easier to work with.

**Order Code** 184861

### Optical System

Optics	fixed optics
Beam angle	25°

### LED Light Sources

LEDs	18x multichip LEDs
Colours	18x red, 18x green, 18x blue, 18x amber
LED lifetime	> 50.000 hours
Colour mixing	RGBA

### Temperature Ranges

Ambient temperature	-20°/+35 °C
Operating temperature	max. 58 °C
Cooling	fan, temperature-controlled

### Controlling and Programming

Protocol	DMX 512-A (RDM)
DMX 512 channels	1/2/3/4/8 (5 modes)
Internal memory	audio/stand-alone programs fixed colours master/slave control
Menu display	8-digit, 2-line LCD
DMX 512 connection	XLR 5-pin

### Technical Details

Mains	100–240 V 47–63 Hz
Power consumption	0,5 A @ 230 V

### Housing

Colour	black
Protection class	IP 65

### Dimensions/Weight

Dimensions (L x W x H)	28,5 x 22,1 x 31 cm
Weight	6 kg
Assembly	compact Y-bracket for hanging and standing installation

### Special Features

- RGBA under one lens
- stand-alone RGBA programming
- memory for last operating status
- easy-to-use menu with LCD
- operating time counter
- default set function
- powerCON True1 IN/OUT

### Included Accessories

- powerCON True1 cable

### Recommended Accessories

- LITECRAFT octo flightcase
- LITECRAFT dodeka flightcase
- LITECRAFT accessory holder
- LITECRAFT 4-leaf barn door
- LITECRAFT omega brackets